

FLAMANT HIGH GLOSS

Description and destination of the product

Flamant High Gloss is an aromatic free lacquer of excellent quality for indoor and outdoor use. This wearproof lacquer can be applied on wood, metals, solid plastics or mineral bases after proper preliminary treatment and priming coat.

Technical data

<u>Binder:</u>	Oil-modified alkyd resins, aromatic-free.
<u>Pigment:</u>	High-grade titanium dioxide and fillers.
<u>Colours:</u>	9 (Flamant High Gloss colour chart or colour fan)
<u>Appearance:</u>	Glossy
<u>Drying times:</u>	Dust-dry: 3.5 hours Dry: 6 -11 hours Repaint: 24 hours

Packing – Transport data: 0,5 L – 1 L - 2,5 L – ADR/RID: 3.31°C / UN nr.: 1263 /IMCO: 3.3 / Flashpoint > 23°C

Theoretic yield: 10-11 m² / L
The practical yield is significantly influenced by the roughness and porosity of the substrate, the applied layer thickness or the losses by airless application.

Use

Flamant High Gloss is best applied by brush (pig's bristles) or special paint roller. Clean equipment with synthetic Thinner. To protect against frost.

Painting conditions

Flamant High Gloss is best applied at temperatures above 12°C and air humidity lower than 65%.



Flamant

THE ORIGINAL PAINT COLLECTION

Any liability based on this technical sheet will be rejected as we are not responsible for the quality of the surface and plication, the condition of the construction nor the application conditions